

TLE SERIES

Feature

- . 100 scale division to show the resistance setting.
- . Enclose in robust sheet metal cover
- . Good linearity
- . Sliding contact of coppers graphite

Specifications

- . Max. Working Voltage: 380VAC, 400VDC
- . Resistance tolerance: $\pm 10\%$
- . Insulation resistance: $> 3 \times 10^9 \Omega$
- . Earthing resistance: $< 0.1 \Omega$
- . Rated resistance: see table

**TLE 600**

Model	Power VA	Resistance (Ω)	Max. Current	Dimensions (W × H × D)	Ceramic Pipe diameter	Weight (kg)
TLE 150	160	10	4A	285 × 140 × 95mm	47mm	1.8
		33	2.2A			
		100	1.25A			
		330	0.7A			
		1000	0.4A			
		3300	0.22A			
TLE 300	320	3.3	10A	385 × 140 × 95mm	47mm	2.4
		10	5.7A			
		33	3.1A			
		100	1.8A			
		330	1.0A			
		1000	0.57A			
		3300	0.31A			
TLE 600	640	10000	0.18A	485 × 160 × 100mm	64mm	3.2
		1.6	20A			
		5	11.4A			
		16.5	6.2A			
		50	3.6A			
		165	2A			
		500	1.1A			
		1650	0.63A			
		5000	0.36A			

TLE SERIES



Feature

- . 100 scale division to show the resistance setting.
- . Good linearity
- . Fused safety socket of the slide bar
- . Enclose in robust sheet metal cover
- . Sliding contact of coppers graphite
- . More tighter structure
- . New appearance design

Specifications

- . Max. Working Voltage: 380VAC, 400VDC
- . Resistance tolerance: $\pm 10\%$
- . Insulation resistance: $> 3 \times 10^9 \Omega$
- . Earthing resistance: $< 0.1 \Omega$
- . Rated resistance: see table



TLE160



TLE300

Model	Power VA	Resistance (Ω)	Max. Current	Dimensions (W×H×D)	Ceramic Pipe diameter	Weight kg
TLE160	160	3.3	7A	240 × 180 × 195mm	64mm	2.2
		10	4A			
		33	2.2A			
		100	1.25A			
		330	0.7A			
		1000	0.4A			
TLE300	320	3300	0.22A	380 × 180 × 100mm	64mm	2.8
		3.3	10A			
		10	5.7A			
		33	3.1A			
		100	1.8A			
		330	1.0A			
TLE600	640	1000	0.57A	480 × 180 × 100mm	64mm	3.5
		3300	0.31A			
		10000	0.18A			
		1.6	20A			
		5	11.4A			
		16.5	6.2A			
		50	3.6A			
		165	2A			
		500	1.1A			
		1650	0.63A			
		5000	0.36A			